

## Very Narrow Aisle Forklift

Used Very Narrow Aisle Forklift Chandler - Warehousing solutions often focus on layout and space saving solutions in order to cut down on costly square footage and decrease travel time required to transport goods throughout the warehouse and loading dock areas. Narrow aisles need specific solutions to allow goods to be accessed and stored properly. More space can be given to storage as less space is needed for accessing the aisle. These warehouse configurations are often referred to as warehouse optimization. Warehouse Optimization There are several significant benefits of implementing very narrow aisle warehouse optimization. Because very narrow forklift trucks were developed to take up less space in maneuvering, it is now possible to decrease warehouse aisle width to less than half the width required by standard forklifts. Numerous narrow aisle forklifts deliver better stacking heights to increase the storage capacity on a square foot basis. This means that costs are decreased because less warehouse space is necessary for the same amount of stock than if a standard aisle configuration were used. Most urban locations have expensive square footage; therefore, reducing costs is a benefit to warehouses and their business. When planned carefully and properly, it is possible to increase warehouse storage area by up to 80 percent by implementing a very narrow aisle width configuration. This warehouse design creates more rack faces and increased product access. Since greater quantities of products are situated in a more accessible area, there is less travel time needed for gathering and storing items. Very narrow aisle layouts and narrow aisle layouts are popular for warehouses. Narrow aisles are measured as those that use fewer than eleven feet of aisle width. Very narrow aisles reduce the aisle width further to around six-and-a-half feet. Both of these aisle widths provide significantly increased storage opportunities. However, they also create challenges when turning within the aisles using forklifts for stocking and order picking. These challenges are met by using very narrow forklifts to gain access and complete tasks. It is necessary to know the dimensions of the aisle when selecting a forklift for a certain job. It is important to have the correct aisle dimensions before forklift shopping to avoid securing a machine that won't fit its' intended location. It is essential to take any columns, posts or utilities into account before deciding a type of narrow aisle forklift design as these can block access. Very Narrow Aisle Forklift Trucks Very narrow aisle forklift trucks are almost always powered electrically, usually by rechargeable battery. Very narrow aisle forklift trucks are popular as stand-up riders to help increase operator comfort and productivity. There are different very narrow aisle forklift designs such as order pickers, reach trucks, wing-mast or turret and end-control riders. Reach Forklift Trucks Reach trucks were designed as a version of the rider stacker forklift but specially modified for use in narrow aisles. It got its name by its function of reaching its forks forward to get to a load. The two kinds of reach trucks the moving carriage and the moving mast. The moving carriage functions by lowering and raising the carriage and the operator. The moving mast works by raising and lowering the forks along the mast, while the operator stays at ground level. Of the two kinds of reach trucks, the moving mast reach truck is the safer of the two varieties. Reach trucks use a pantograph system, a type of jointed framework, which allows the operator to reach for or place a load without the need to move the forklift itself. Order Pickers Order pickers have been designed and developed specifically for use in picking orders from high, typically hard-to-reach racks. They are used for smaller picking items that can be lifted and moved by hand. Order pickers elevate the operator to the level of goods to pick and identify particular items required for filling an order. End-Control Riders End-control riders are machines that pick loads up at floor level and move the items horizontally as opposed to lowering or lifting over numerous heights. Turret or Swing-Mast Forklift Swing-mast or turret very narrow aisle forklifts feature an articulating swivel mast that pivots. The mast swivels to enable pallets to be positioned on the right or left side of the forklift. Guided Very Narrow Aisle Trucks Many very narrow aisle forklift trucks are able to be guided down aisles by wire or rail. Since the forklift truck is guided, the chance of colliding with racks while traversing down the aisles is very low. In rail-guided models, sets of rails are

placed into the floor on each side of the aisle. They run the length of the aisle and also curve around the aisles' edge. Wheel guides on the forklift slide into the floor rails to stop the machine from traveling out of bounds. Running down the center of the aisle, wire-guidance forklifts rely on floor wires instead of rails. Narrow aisle forklifts rely on a wire-guide system to help it communicate with the floor wires. This allows the machine to be steered by the wires, stopping it from traveling outside of the specific location. Work Site Considerations There are a few critical considerations when implementing a very narrow aisle configuration. The floor and the rack construction needs to be evaluated to avoid any issues since the very narrow aisle units have extremely high racking systems. There are four main locations that need to be ideally prepared before any racking system can be installed. These areas need to be monitored continuously including fixing cracks in the floor, ensuring the racks are straight, a level floor and an appropriate load capacity of the floor. Level Floor Because of the height of the racking systems, any slight slope of the floor is likely to negatively affect the plumbness of the racks, especially over time when loads are continuously placed and removed on the racks. Without a level floor foundation, the rack stability could be compromised. Crack Repair When there are floor cracks found, they need to be assessed and immediately fixed for safety concerns. Cracks may affect the floor's level and, when they are approximately 3/8 inches wide, will need to be properly filled with a material at least as hard as the surrounding floor. Floor Load Capacity The floor should meet certain minimum requirements before considering a narrow aisle configuration. At a minimum, the floor should consist of 3,000 psi concrete as well as contain evenly distributed rebar approximately 3 to 4 inches below the surface. Depending on the configuration and load requirements, extra reinforcements may be necessary. Plumb Racks Of great importance is the proper installation of the racking system. Rack failure can happen if they are improperly installed. One of the most important details to ensure proper installation, is that all racks are plumb. If necessary, rack shims should be used to ensure the racks are plumb within 1 inch at the 30 foot height of the racks. If the above measures are not taken or are improperly implemented, it is likely to cause a racking failure. Racking failure can kill or injure employees, damage equipment and result in horrible damage. These measurements are vital to the success of installing a safe and productive narrow aisle configuration.